

Speedlink HR trigger snap shackle - Webbing eye - Length: IO2 mm

Part #2754





Description

Make the right choice!

Speedlink is the new trigger snap shackle offering an excellent weight / performance ratio. Its specific shape makes it perfect for foresail tack points.

Ultra lightweight: developed by using finite element analysis software, Speedlink has an optimised design thanks to its shape, cut-outs and ribs. Its make it extremely design and gives its one of the best strength/weight ratios on the market. Easy opening: opening under load, whether manually or using release fid, is easy and effortless thanks to the generous passage diameter and its optimised slopes.

No accidental opening: the special shape of the latch reduces inertia and avoids unintentional opening, especially under impact.

Sturdy: Speedlink is forged in HR stainless steel and can bear outstanding working and breaking loads for a minimum weight.

Modern design: its ultra-technical lines avoid excessive rope wear and prevent adjacent lines from jamming.

Applications

Foresail tack points.

Technical information

Materials	HR 17.4 PH stainless steel grade
Length (mm)	102
Working load (kg)	2320
Breaking load (kg)	5400
Weight (g)	174
A (mm)	21
B (mm)	17
C (mm)	35

Caption



...

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only. The safety factor is 5 times the breaking load. WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures