

HR snap shackle - Large bail - Length: I40 mm

Part #2377





Description

HR Forged snap shackle (Grade 17.4 PH stainless steel) with large eye $% \left({{\left[{{{\rm{S}}_{\rm{T}}} \right]}_{\rm{T}}} \right)$

The large eye allows to attach several ropes

Free rotation of the snap shackle thanks to the swivel eye The plunger pin is set captive into the hook and cannot

become detached

Excellent working and breaking loads

Easy to open by pulling the plunger pin (possiblity to attach a lanyard)

Applications

Snap shackle applications

Applications requiring a free rotation of the snap shackle (for a better sail orientation)

Technical information

Δ

| Materials | HR 17.4 PH stainless steel grade |
|--------------------|----------------------------------|
| Length (mm) | 140 |
| Working load (kg) | 2800 |
| Breaking load (kg) | 7500 |
| Weight (g) | 398 |
| A (mm) | 26 |
| B (mm) | 35 |

Caption



Working load (WL) : for nautical applications

Worki applic

Working Load Limit (WLL): for industrial applications only. The safety factor is 5 times the breaking load.

WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.