


Captive pin bow shackle - Dia 10 mm

Part #1445



Description

Captive pin bow shackle forged in grade 316L stainless steel
The pin is connected to the body at all times even when opened
The pin is locked into one of the indentations
No risks of loose due to vibrations
Outstanding working and breaking loads
Single handed operation for more safety
WLL: only for industrial applications (lifting i.e...)
CE marking and batch number

Applications

To be used when ample room is required
Possibility to attach several lines or cables

Technical information

Materials	316 stainless steel grade
 Working load (kg)	1520
 WLL (kg)	1040
Breaking load (kg)	5200
Weight (g)	139
A (mm)	46
B (mm)	20
C (mm)	11
D (mm)	21
D diameter (mm)	10
E (mm)	9
M (mm)	52

Caption

-  Working load (WL) : for nautical applications
-  Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.