



## 1nm portside lights for vessels (Under 12 Meters)

### 1 NM Portside lights

1nm port, silver and black anodized

Vertically mounted with 2,5m cable

### Specifications

**Number** 1 NM Portside lights

**Light Color** Red

**Dimensions metric** 92,5 x 28 x 49,7

**Certification** This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on [www.lopolight.com/under-support](http://www.lopolight.com/under-support)

**Intensity** >1,2cd

**Dimensions imperial** 3.6" x 1.1" x 1.95"

**Approved to** COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

**Visibility** 1nm

**Included In Package** 1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide

**Operating temperature** -25°C to 55°C

**Mounting** Vertical

**Materials** Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

**Operating Voltage** 10-32VDC

**EAN** 5704438009936

**IP rating** IP68

**Power draw (W)** 1,1

**UPC Code** 879343009939

**Connection** 2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	60
Current consumption (mA @ 24VDC)	32
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.39 Kg
Weight (Oz)	13.76 Oz



## 1nm 112,5° Red, port, black anodized w/6m cable

101-002-B 6M

1nm port, silver and black anodized  
Vertically mounted with 6m cable

Specifications	
Number	101-002-B 6M
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com/underSupport">www.lopolight.com/underSupport</a>
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438016194
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343016203
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	60
Current consumption (mA @ 24VDC)	32
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.6 Kg
Weight (Oz)	21.16 Oz



## 1nm 112,5° Red, port, black anodized

101-002-B

1nm port, silver and black anodized  
Vetically mounted with 2,5m cable

Specifications	
Number	101-002-B
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com/underSupport">www.lopolight.com/underSupport</a>
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009943
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343009946
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	60
Current consumption (mA @ 24VDC)	32
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.39 Kg
Weight (Oz)	13.76 Oz



## 1nm 112,5° Red, port, black anodized

101-002-B-SUB

1nm port, silver and black anodized  
Vertically mounted with 2.5m cable  
Potted under vacuum, submersible light

Specifications	
Number	101-002-B-SUB
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com/underSupport">www.lopolight.com/underSupport</a>
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438019133
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343019266
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	60
Current consumption (mA @ 24VDC)	32
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.38 Kg
Weight (Oz)	13.40 Oz





## 1nm 112,5° Red, port, silver anodized w/6m cable

101-002 6M

1nm port, silver and black anodized  
Vertically mounted with 6m cable

Specifications	
Number	101-002 6M
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com/underSupport">www.lopolight.com/underSupport</a>
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438016187
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343016197
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	60
Current consumption (mA @ 24VDC)	32
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.6 Kg
Weight (Oz)	21.16 Oz



## 1nm 112,5° Red, port, silver anodized

101-002

1nm port, silver and black anodized  
Vertically mounted with 2,5m cable

Specifications	
Number	101-002
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com/underSupport">www.lopolight.com/underSupport</a>
Intensity	>1,2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009936
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343009939
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	60
Current consumption (mA @ 24VDC)	32
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.39 Kg
Weight (Oz)	13.76 Oz