



2nm 112,5° Green, Starboard, black w/FB base

301-008-FB-B

2nm Starboard, black w/FB base
Horizontally mounted with 2,5m cable
FB (flat base) POM mounting system

Specifications	
Number	301-008-FB-B
Light Color	Green
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com/underSupport
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide,precabled with 2.5 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043688
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343043810
Connection	2.5m cable
Current consumption (mA @ 12VDC)	110

Specifications	
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.57 Kg
Weight (Oz)	20.21 Oz