



## 2nm 112,5° Green, Starboard, black w/FB base

301-008-FB-B 6M

2nm Starboard, black w/FB base  
Horizontally mounted with 6m cable  
FB (flat base) POM mounting system

### Specifications

**Number** 301-008-FB-B 6M

**Light Color** Green

**Certification** This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on [www.lopolight.com](http://www.lopolight.com) under [Support](#)

**Approved to** COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

**Included In Package** 1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide

**Operating temperature** -25°C to 55°C

**Mounting** Horizontal

**Materials** Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

**Operating Voltage** 10-32VDC

**EAN** 5704438044456

**IP rating** IP68

**Power draw (W)** 1,4

**UPC Code** 879343044589

**Connection** 2.5m cable

**Current consumption (mA @ 12VDC)** 110

**Current consumption (mA @ 24VDC)** 60

**Vessel size** 12-20M,20-50M

**Min. feed wire gauge** 0.5mm2 AWG22

Specifications	
Weight (Kg)	0.71 Kg
Weight (Oz)	25.08 Oz