



2nm 112,5° Red, Port, black w/FB base

301-009-FB-B

2nm Port, black w/FB base
Horizontally mounted with 2,5m cable
FB (flat base) POM mounting system

Specifications

Number 301-009-FB-B

Light Color Red

Dimensions metric Ø92,5mm x 36mm

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com/underSupport

Dimensions imperial Ø3.6" x 1.4"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 2nm

Included In Package 1 Navigation light,Installation guide,precabled with 2.5 meter shielded marine grade cable

Operating temperature -25°C to 55°C

Mounting Horizontal

Operating Voltage 10-32VDC

EAN 5704438043862

IP rating IP68

Power draw (W) 1,2

UPC Code 879343043995

Connection 2.5m cable

Current consumption (mA @ 12VDC) 90

Current consumption (mA @ 24VDC) 50

Specifications

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 0.57 Kg

Weight (Oz) 19.93 Oz