



## 2nm Comb Side + 360° White, 6M w/FB base

201-003+012-FB 6M

2nm Comb Side + 360° White, 6M w/FB base  
Horizontally mounted with 6m cable  
FB (flat base) POM mounting system

Specifications	
Number	201-003+012-FB 6M
Light Color	Red,Green
Dimensions metric	Ø92,5mm x 58mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Support</a>
Dimensions imperial	Ø3.6" x 2.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043312
IP rating	IP68
Power draw (W)	2.6
UPC Code	879343043445
Connection	6m cable
Current consumption (mA @ 12VDC)	163

Specifications	
<b>Current consumption (mA @ 24VDC)</b>	90
<b>Vessel size</b>	12-20M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	1.07 Kg
<b>Weight (Oz)</b>	37.86 Oz