




2nm 2x112,5° Red/Green Sidelight, black w/FB base

201-003-FB-B

2nm Comb Sidelights, black w/FB base
Horizontally mounted with 2,5m cable
FB (flat base) POM mounting system

Specifications	
Number	201-003-FB-B
Light Color	Red, Green
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72, EN14744, IEC 60945, IACS E10, USCG, ABS, M.E.D., DNV, LR
Visibility	2nm
Included In Package	1 Navigation light, Installation guide, precabled with 2.5 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043299
IP rating	IP68
Power draw (W)	2,2
UPC Code	879343043421
Connection	2.5m cable
Current consumption (mA @ 12VDC)	163

Specifications	
Current consumption (mA @ 24VDC)	90
Vessel size	12-20M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.55 Kg
Weight (Oz)	19.26 Oz