



2nm 225° White, Masthead, silver anodized

201-010

2nm masthead, vert mnt, 0.7m
Vertically mounted with 0,75m cable

Specifications	
Number	201-010
Light Color	White
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopelight.com under Support
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010208
IP rating	IP68
Power draw (W)	2
UPC Code	879343010201
Connection	0.7m cable
Current consumption (mA @ 12VDC)	137

Specifications	
Current consumption (mA @ 24VDC)	80
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.42 Kg
Weight (Oz)	14.81 Oz