



2nm 225° White, Masthead + 6W Decklight, silver

201-010DLXI 15M

Vertical mounted with 15m cable
Decklight angled 25° forward
Decklight lightbeam is 26°

Specifications

Number 201-010DLXI 15M

Dimensions metric 54 x 38,7 x 72,2

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on [www.lopolight.com/under Support](http://www.lopolight.com/under%20Support)

Dimensions imperial 2.1" x 1.5" x 2.8"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Included In Package 1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide

Operating temperature -25°C to 55°C

Mounting Vertical

Materials Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 10-32VDC

EAN 5704438043909

IP rating IP68

Power draw (W) 2,2

UPC Code 879343044039

Connection 2.5m cable

Current consumption (mA @ 12VDC) 163

Stock status Made to order

Current consumption (mA @ 24VDC) 90

Specifications

Min. feed wire gauge	0.5mm2 AWG22
-----------------------------	--------------

Weight (Kg)	1.43 Kg
--------------------	---------

Weight (Oz)	50.44 Oz
--------------------	----------