



2nm 225° White, Masthead, silver w/FB base

201-010KL-FB

2nm Masthead, silver anodized w/FB base
Horizontally mounted with 0,7m cable
FB (flat base) POM mounting system

Specifications	
Number	201-010KL-FB
Light Color	White
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com/underSupport
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043381
IP rating	IP68
Power draw (W)	2
UPC Code	879343043513
Connection	0.7m cable
Current consumption (mA @ 12VDC)	137

Specifications	
Current consumption (mA @ 24VDC)	80
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.48 Kg
Weight (Oz)	16.89 Oz