



2nm 225° White, Masthead, black anodized w/FB base

201-010KL-FB-B

2nm Masthead, black anodized w/FB base
Horizontally mounted with 0,7m cable
FB (flat base) POM mounting system

| Specifications | |
|----------------------------------|--|
| Number | 201-010KL-FB-B |
| Light Color | White |
| Dimensions metric | Ø92,5mm x 36mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com/underSupport |
| Dimensions imperial | Ø3.6" x 1.4" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 2nm |
| Included In Package | 1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438043398 |
| IP rating | IP68 |
| Power draw (W) | 2 |
| UPC Code | 879343043520 |
| Connection | 0.7m cable |
| Current consumption (mA @ 12VDC) | 137 |

| Specifications | |
|----------------------------------|--------------|
| Current consumption (mA @ 24VDC) | 80 |
| Vessel size | Under 12M |
| Min. feed wire gauge | 0.5mm2 AWG22 |
| Weight (Kg) | 0.48 Kg |
| Weight (Oz) | 16.89 Oz |