



2nm 180° Green, silver anodized

200-018G2 6M

2nm 180° Green, black anodized
Vertically mounted with 6m cable

Specifications	
Number	200-018G2 6M
Light Color	Green
Dimensions metric	104 mm x 37 mm x 45 mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	4.0" x 1.4" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438019300
IP rating	IP68
Power draw (W)	1,5
UPC Code	879343019433
Connection	6m cable

Specifications	
Current consumption (mA @ 12VDC)	145
Stock status	Made to order
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.48 Kg
Weight (Oz)	16.93 Oz