



## 2nm 180° Red, silver anodized

200-016G2

2nm 180° Red, silver anodized  
Vertical mounted with 0.75m cable

| Specifications        |  |
|-----------------------|--|
| Number                | 200-016G2  |
| Light Color           | Red  |
| Dimensions metric     | 104 mm x 37 mm x 45 mm   |
| Certification         | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support |
| Intensity             | >5.4cd   |
| Dimensions imperial   | 4.0" x 1.4" x 1.8"   |
| Approved to           | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR   |
| Visibility            | 2nm  |
| Included In Package   | 1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide  |
| Operating temperature | -25°C to 55°C  |
| Mounting              | Vertical   |
| Materials             | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane  |
| Operating Voltage     | 10-32VDC   |
| EAN                   | 5704438012158  |
| IP rating             | IP68   |
| Power draw (W)        | 1,5  |
| UPC Code              | 879343012151   |
| Connection            | 0.7m cable   |

| Specifications                   |                         |
|----------------------------------|-------------------------|
| Current consumption (mA @ 12VDC) | 145                     |
| Stock status                     | Usually in stock        |
| Current consumption (mA @ 24VDC) | 60                      |
| Vessel size                      | Under 12M,12-20M,20-50M |
| Min. feed wire gauge             | 0.5mm2 AWG22            |
| Weight (Kg)                      | 0.34 Kg                 |
| Weight (Oz)                      | 11.99 Oz                |