



2nm 180° White, black anodized

200-024G2-B

2nm 180° White, black anodized
Vertical mounted with 0.75m cable

Specifications	
Number	200-024G2-B
Light Color	White
Dimensions metric	104 mm x 37 mm x 45 mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopelight.com under Support
Intensity	>5.4cd
Dimensions imperial	4.0" x 1.4" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,USCG
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438021037
IP rating	IP68
Power draw (W)	2,4
UPC Code	879343021160
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	137
Lead time	1-2 weeks
Current consumption (mA @ 24VDC)	80
Vessel size	Under 12M,12-20M,20-50M
Weight (Kg)	0.34 Kg
Weight (Oz)	11.99 Oz