



2nm 2x112,5° Red/Green Sidelight, silver anodized

201-004

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

<>

Vertically mounted with 2,5m cable

Specifications	
Number	201-004
Light Color	Red,Green
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012479
IP rating	IP68
Power draw (W)	2,2
UPC Code	879343012472
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	163
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	90
Vessel size	12-20M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.5 Kg
Weight (Oz)	17.64 Oz